



Kvs/Cv flow coefficients · RPV Series 62, 72, 73, 82

Inhalt

1 Kvs/Cv · Series 72, 73, 82.....2

1.1 Seat with metal sealing · Flow to open (FTO)2

1.2 Seat with metal sealing · Flow to close (FTC)2

1.3 Seat with soft sealing · Flow to close (FTC)3

2 Kvs/Cv · Series 62.....4

2.1 Seat with metal sealing · Flow to open (FTO)4

2.2 Seat with soft sealing · Flow to open (FTO)4

3 Kvs/Cv · Type tested valves 72.3, 72.4, 82.7 (GAR, DVGW, EN 161)5

3.1 Seat with soft sealing · Flow to close (FTC)5

1 Kvs/Cv · Series 72, 73, 82

1.1 Seat with metal sealing · Flow to open (FTO)

Size	DN	25	40	50	80	100	150	200	250	300	350	400	500	600
	NPS	1	1 ½	2	3	4	6	8	10	12	14	16	20	24
Seat factor	Flow coefficient													
100 %	Kvs	16	36	70	220	360	720	1100	1950	2700	3400	4700	6700	11000
	Cv	18	42	81	254	416	832	1272	2254	3121	3930	5434	7746	12717
	Seat Ø mm	18	26	36	60	76	105	135	170	210	245	290	350	420
60 %	Kvs	12	22	43	145	210	430	630	1230	1500	2050	2700	3800	5800
	Cv	14	25	50	168	243	497	728	1422	1734	2370	3121	4393	6705
	Seat Ø mm	16	21,5	29,5	50	60	86	106	146	163	195	225	271	330
40 %	Kvs	10	16	31	105	150	275	390	850	900	1350	1600	2300	3550
	Cv	12	18	36	121	173	318	451	983	1040	1560	1850	2659	4104
	Seat Ø mm	14	18,5	25,5	44	53	73	88	126	133	165	184	221	275
25 %	Kvs	4	12	19	70	100	185	245	500	640	820	1100	1250	2680
	Cv	4,6	14	22	81	116	214	283	578	740	950	1272	1445	3098
	Seat Ø mm	10	16	21	37	45	62	73	102	116	135	160	175	245

1.2 Seat with metal sealing · Flow to close (FTC)

Size	DN	25	40	50	80	100	150	200	250	300	350	400	500	600
	NPS	1	1 ½	2	3	4	6	8	10	12	14	16	20	24
Seat factor	Flow coefficient													
100 %	Kvs	16	36	70	210	340	660	810	1300	2100	2320	3400	4800	7500
	Cv	18	42	81	243	393	763	936	1503	2428	2700	3931	5549	8671
	Seat Ø mm	18	26	36	60	76	105	135	170	210	245	290	350	420
60 %	Kvs	12	22	43	135	200	320	410	820	900	1370	1800	2700	3700
	Cv	14	25	50	156	231	370	474	948	1040	1590	2081	3121	4277
	Seat Ø mm	16	21,5	29,5	50	60	86	106	146	163	195	225	271	330
40 %	Kvs	10	16	31	95	120	185	250	540	570	880	1120	1600	2350
	Cv	12	18	36	110	139	214	289	624	659	1020	1295	1850	2717
	Seat Ø mm	14	18,5	25,5	44	53	73	88	126	133	165	184	221	275
25 %	Kvs	4	12	19	56	90	125	160	320	410	530	860	870	1800
	Cv	4,6	14	22	65	104	145	185	370	474	615	994	1006	2081
	Seat Ø mm	10	16	21	37	45	62	73	102	116	135	160	175	245

1.3 Seat with soft sealing · Flow to close (FTC)

Size	DN	25	40	50	80	100	150	200	250	300	350	400	500	600
	NPS	1	1 ½	2	3	4	6	8	10	12	14	16	20	24
Seat factor	Flow coefficient													
100 %	Kvs	12	36	68	180	290	535	730	1220	2000	On request	2700	4800	11000
	Cv	14	42	79	208	335	618	844	1410	2312		3121	5549	12717
	Seat Ø mm	16	26	35	54	70	98	128	160	204		270	350	420
60 %	Kvs	11	22	43	135	200	320	410	820	900		1800	2700	3700
	Cv	13	25	50	156	231	370	474	948	1040		2081	3121	4277
	Seat Ø mm	15	21,5	29,5	50	60	86	106	146	163		225	271	330
40 %	Kvs	10	16	31	105	120	185	250	540	570		1120	1600	2350
	Cv	12	18	36	121	139	214	289	624	659		1295	1850	2717
	Seat Ø mm	14	18,5	25,5	46	53	73	88	126	133		184	221	275
25 %	Kvs	4	12	19	56	90	125	160	320	410		860	870	1800
	Cv	4,6	14	22	65	104	145	185	370	474		994	1006	2081
	Seat Ø mm	10	16	21	37	45	62	73	102	116		160	175	245

2 Kvs/Cv · Series 62

2.1 Seat with metal sealing · Flow to open (FTO)

Size	DN	25	40	50	80	100	150	200
	NPS	1	1½	2	3	4	6	8
Seat factor	Flow coefficient							
100 %	Kvs	16	36	80	243	386	703	968
	Cv	18	42	92	281	446	813	1119
	Seat Ø mm	18	26	36	60	76	105	135
40 %	Kvs	10	17	32	104	148	265	348
	Cv	12	20	37	120	171	306	402
	Seat Ø mm	14	18,5	25,5	44	53	73	88

2.2 Seat with soft sealing · Flow to open (FTO)

Size	DN	25	40	50	80	100	150	200
	NPS	1	1½	2	3	4	6	8
Seat factor	Flow coefficient							
100 %	Kvs	11	34	80	212	364	636	904
	Cv	13	39	92	245	421	735	1045
	Seat Ø mm	14	23	35	55	70	95	125
40 %	Kvs	-	17	32	104	148	265	348
	Cv	-	20	37	120	171	306	402
	Seat Ø mm	-	18,5	25,5	44	53	73	88

3 Kvs/Cv · Type tested valves 72.3, 72.4, 82.7 (GAR, DVGW, EN 161)

3.1 Seat with soft sealing · Flow to close (FTC)

Size	DN	25	40	50	80	100	150	200
	NPS	1	1 ½	2	3	4	6	8
Seat factor	Flow coefficient							
100 %	Kvs	12	26	68	180	290	320	410
	Cv	14	30	79	208	335	370	474
	Seat Ø mm	16	26	35	54	70	86	106
60 %	Kvs	11	21	43	156	242	185	291
	Cv	13	24	50	180	280	214	336
	Seat Ø mm	15	21	29,5	52	65	73	92
40 %	Kvs	10	17	37	105	200	125	250
	Cv	12	20	43	121	231	145	289
	Seat Ø mm	14	19	27,5	46	60	62	88



VETEC Ventiltechnik GmbH
Siemensstrasse 12 · 67346 Speyer · Germany
Phone: +49 6232 6412-0 · Fax: +49 6232 42479
E-mail: sales-vetec-de@samsongroup.com
Internet: vetec.samsongroup.com